



STONELEAF SLATES

Health & Safety

The following information is based on recommendations issued by the Health and Safety Executive who can be contacted at:

The HSE Information Centre
Broad Lane, Sheffield
South Yorks. S3 7HQ
Tel: 0114 289 2345
Fax: 0114 289 2333

1. Safe Use of Ladders

Any work that cannot be safely done from a ladder should be done from secure access equipment or scaffolding. The ladder should rest against a secure surface and strapped to the structure. For further information on this, refer to BS 1129: 1982, BS2037: 1984, HSE Guidance Note GS31.

2. Safe Use of Scaffolds

It is the responsibility of the contractor to provide a safe working environment for operatives. It is particularly important that the right type of scaffolding is used and that this is securely connected to the work area of the building. The various types of scaffolding ties are clearly set out in the following documents:

HSE General Access Scaffolding Guidance Note 5

Scaffolders' and Users Guide to Access Scaffolding BEC Publications

BS5973: 1990 Code of practice for Access and Special Scaffold in Steel

Tower Scaffolds are covered in the following documents:

HSE Tower Scaffolds Guidance Note GS42

Operators Code of Practice Prefabricated Aluminium Scaffolding Manufacturers' Association

3. Working on Pitched Roofs

Working on a pitched roof surface is an extremely dangerous environment. As well as providing adequate scaffolding, the operator should wear an approved harness if at all practicable and have use of roof ladders and boards. For further information refer to the following documents:

NS1397: 1979 Specifications for Industrial Safety Belts, Harnesses and Safety Lanyards

BS5062: Part 1: 1985 "Roofing and Cladding in Windy Conditions"

Health and Safety Statement

This information is provided in compliance with the Health and Safety at Work Act 1974 Section 8 (as amended by Consumer Protection Act 1987) and control of substances Hazardous to health (COSHH) 1988.

1. The product is natural roofing slates used as a weathering seal for roofs and wall claddings.
2. The slate is composed of certain mountain sites and is composed of various minerals such as quartz, Sericite, Chlorite, Feldspar and Calcite.
3. If dust is inhaled in excessive amounts, over many years, during the manufacturing process it can, without proper controls, possibly create a long term health hazard. In context of site work the only potential hazard is sharp edges and splinters. Precautions to be taken in areas of restricted ventilation are dust masks to BS 2091. Eye protection during cutting to BS 2092 grade 2.
4. Wear gloves during handling to avoid slate splinters and knee protectors during fixing. Store no more than 2 pallets high.

Stoneleaf Slates is Trading name of Stoneleaf Building Materials Ltd., Company Registered in England
No.3877699